

ISO 12924: L-XC(F)CIB2
DIN 51502: KP2K-30

**CORROSION
PROTECTION**

**EXTREME
PRESSURE**

**MULTI
PURPOSE**

**WATER
RESISTANCE**

PRODUCT DESCRIPTION

Greenlube EP-2 Lithium-Free is an anhydrous calcium thickened lubricating grease based on a mineral oil. The grease contains antioxidants, corrosion inhibitors and EP/AW additives.

The thickener, together with the special base oil blend, makes the product suitable for the lubrication of medium loaded bearings and in wet and corrosive environments. The lubricating grease has excellent adhesion and water resistance.

Greenlube EP-2 Lithium-Free is a high quality multipurpose grease that can be used in both industrial and automotive applications. The grease is suitable for a wide range of plain and rolling bearings.

Excellent water resistance
Very good corrosion protection
Wide range of use

TYPICAL TECHNICAL DATA

Thickener	Anhydrous calcium	
Base fluid	Mineral oil	
Texture	Smooth	
Colour	Visual	Yellow brown
NLGI Grade	ASTM D 217	2
Dropping point	IP 396	> 140°C
Base oil viscosity at 40°C	ASTM D 7152	220 mm ² /s
Base oil viscosity at 100°C	ASTM D 7152	15 mm ² /s
Penetration 60 strokes	ISO 2137	265 - 295
4-ball weld load	DIN 51350:4	3000 N
Water resistance at 90°C	DIN 51807:1	0
Water wash out at 79°C	ISO 11009	< 10 %
Emcor salt water	ISO 11007	≤ 2 - 2
Flow Pressure at -30°C	DIN 51805	< 1400 mbar
FE9 (B/130°C/6000rpm/1500N)	DIN 51821	F50 ≥ 100 h
Density	IP 530	920 kg/m ³
Temperature range	-30°C to +130°C	

Information and data can be changed without previous notification. This information replaces prior editions

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only.

05-03-2024

For further information, please contact

Groeneveld Transport Efficiency B.V.

Stephensonweg 12
4207 HB Gorinchem
The Netherlands

Telephone: +31 (0) 183 641 400

Email address: info@groeneveld-beka.com

Website: www.groeneveld-beka.com